



Lusterclean 35

Lusterclean 35 is a mildly alkaline, water soluble, liquid product developed for cleaning all metals (except magnesium) without affecting their luster.

The special blend of detergents in Lusterclean 35 will emulsify and disperse soils such as lard oil, sulfurized and chlorinated oils, general shop oil and certain identification inks present on aluminum alloys.

The other feature of Lusterclean 35 is its ability, when used hot with agitation, or as an ultrasonic cleaner, to remove buffing compounds from aluminum, brass, bronze, steel, stainless steel, and zinc die-castings.

Note: Lusterclean 35 is an excellent pre-soak cleaner. However, it will not clean to a no water-break surface. Thus, Lusterclean 35 would find applications where the requirements are such that a no water-break surface is not required. Furthermore, the residual invisible film on the surface of the metal does possess limited corrosion preventative properties. This invisible film is immediately removed in an alkaline soak cleaner such as Cleaner 187B, CB-1, 520A OR 520B.

Features & Benefits

Fast acting cleaner-parts are cleaned rapidly	Safe to use-mildly alkaline and non-flammable
-----------------------------------------------	-----------------------------------------------

Operating Conditions

Concentration	3% – 10% (vol)
Temperatures	150°F – 200°F (65°C – 93°C)
Time	2 – 10 min
Equipment	Mild steel tank and heating coils
Agitation	Required for removal of buffing or polishing compounds
Ventilation	Not required

Ultrasonic cleaning

Concentration	3% – 5% (vol) max.
---------------	--------------------



Temperature range	140°F – 160°F (60°C – 71°C)
Time	30 sec – 1 ½ min

Titration Method

1. Pour a 100 mL sample of Luster Clean 35 into a 250 mL Erlenmeyer flask. Use 100 mL graduate to dispense solution.
2. Add 1 mL LaMotte Yellow indicator - swirl flask to ensure complete mixture.
3. Titrate with 0.5 N HCL or Sulfuric Acid until the solution turns from yellow to pink.
4. Record mL of acid used.

Calculation

$$\text{Concentration Lusterclean 35} = 0.58 \times \text{mL } 0.5 \text{ N HCl Used}$$

Test Kit Method

1. Fill test bottle 1/2 full of water
2. Using syringe, add 10 mL of Lusterclean 35 solution.
3. Add 4 to 8 drops Methyl Orange Indicator.
4. Add 0.72 N Hydrochloric Acid drop wise.
5. Record drops of 0.72 N Hydrochloric Acid required to change solution from yellow to orange.

Calculation

$$\text{Luster Clean 35} = 0.46 \times \text{Drops } 0.72 \text{ N Hydrochloric Acid}$$

Waste Disposal

Discharge to a disposal system. In order to be completely informed of the latest regulations for your area, please contact the local authorities.

Caution

Lusterclean 35 is a mildly alkaline product and should be handled accordingly. Avoid skin and eye contact. Wear protective clothing, goggles, and gloves. Flush exposed areas immediately with clean cold water. Contact a doctor promptly in case of injury.



WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

**For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com**

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶